

### Model: WR6500

# BE6500 Gigabit Wi-Fi 7 Router





Datasheet



### Supercharged Speed. Blazing-Fast Wi-Fi.

For the first time, MLO in Wi-Fi 7 connects clients through multiple bands simultaneously, aggregating the speed and making congestion on any single band insensible. In addition, the 4K-QAM boosts speed by another 20%, delivering a total of 2.7X faster speed for smoother experience in larger homes.



### **Immersive Gaming with Lower Latency**

The enhanced OFDMA with multi-RU and puncturing utlize non-busy frequency resource unit to fit more connections at the same time.



### Powerful Wi-Fi 7 Chip for Responsive Network

The next-gen Wi-Fi 7 Broadcom CPU with fabulous efficiency processes more tasks instantly, keeping network super-capable and responsive.




#### Versatile Management

**Parental Control** Set up profiles with corresponding policies to establish a safer network for your loved ones.



CUDU

Support the IPv6 services by your ISP and browse the IPv6 websites with faster performance.



**Cudy APP Control** Manage your network right on your phone. This device supports cloud remote management.



Includes Tag VLAN to support assigning IPTV/VoIP ports. IGMP snooping

Set speed limits for certain clients to prioritize your gaming rigs and other important devices.

improves IPTV network efficiency.



# Highlights

A dual-band WiFi 7 router with an aggregate of 6.5 Gbps speed, and five Gigabit ports, catering to super-fast internet access, gaming, and entertainment scenarios.

	, 0	
<ul> <li>Broadcom 2 GHz Quad-Core CPU</li> </ul>		DDR/RAM
<ul> <li>6-Stream Dual-Band Wi-Fi 7</li> </ul>	Wireless	5 GHz Wi-Fi Sp
• 5760 Mbps + 688 Mbps Wi-Fi		2.4 GHz Wi-Fi S
<ul> <li>5× Gigabit Ethernet Ports</li> </ul>		5 GHz Wi-Fi Str
<ul> <li>200 Connected Devices</li> </ul>		2.4 GHz Wi-Fi S
• Covers 140 m² (1,500 ft²)		Wi-Fi Antennas
<ul> <li>Cudy Mesh, VPN Server and Client</li> </ul>		5 GHz Antenna
		2.4 GHz Antenna
<ul> <li>Cudy App, Cloud Control</li> </ul>		FEM or PA/LNA
* Cudy Mesh will be supported in June, 2025 with cloud Firmware upgrade.		

### Package Content

- WR6500
- Power Adapter
- Ethernet Cable
- Installation Guide

# Hardware Specs

CPU	Chipset	BCM6766
	CPU Details	2.0 GHz Quad-core, ARM Cortex-A7
Memory/Storage	Flash/ROM	128 MB (1 Gbit) NAND
	DDR/RAM	512 MB (4 Gbit) DDR4
Wireless	5 GHz Wi-Fi Speed	5765 Mbps
	2.4 GHz Wi-Fi Speed	688 Mbps
	5 GHz Wi-Fi Streams	4T4R (4×4 MIMO)
	2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
	Wi-Fi Antennas	6× Fixed
	5 GHz Antenna Gain Max	5.27dBi
	2.4 GHz Antenna Gain Max	5.19dBi
	FEM or PA/LNA	5 GHz: 4× External
		2.4 GHz: 2× External
	Beamforming	True
	Range Performance	Max: 240 m (787 ft)
		Indoor WiFi range varies depending on the
		layout and wall materials. See Wall
		Performance spec for placement suggestions
	Wall Performance	Two wooden walls with thickness < 10 cm (4'')
		One concrete wall with thickness < 20 cm (7'')
		or two concrete walls with thickness < 10 cm (4'')



# Hardware Specs

Interfaces	Gigabit RJ45 Ports	5	Certifications	FCC, CE	
	Ethernet Notes	1× WAN port, the rest are LAN ports	Mechanical	Installation	Desktop
	LED	System			Wall-mount
		Internet		Dimension	253×152.5×48.2 mm
		Wi-Fi			9.96×6×1.9 inches
		WPS		Product Weight	580.0 g (20.46 oz.)
	Physical Buttons	Power On/Off Button	Ordering Information	Retail Package Weight	EU: 1190.0 g (41.98 oz.)
		WPS Button		Retail Package Dimension	431×324×58 mm
		Reset Button			16.97×12.76×2.28 inches
	Power Input	DC Jack		Units per Carton	8
Power	Power Methods	DC		Carton Dimension	49.2×44.5×34.4 cm
	DC	12V 1.5A			19.37×17.52×13.54 inches
	Power Adapter	Input: 100 ~ 240 V, 50/60 Hz AC		Carton Gross Weight	EU: 10.5 kg (23.15 lbs)
		Output: 12V 1.5A DC		Carton Net Weight	EU: 9.5 kg (20.94 lbs)
	Max Power Consumption (W)	17W			
Reliability	Environment	Operating Temperature:			
		0 °C ~ 40 °C (32 °F ~104 °F)			
		Storage Temperature:			
		-40 °C ~ 70 °C (-40 °F ~ 158 °F)			
		Humidity: 10% ~ 90% non-condensing			
		Storage Humidity: 5% ~ 95% non-condensing			

# cudy

# Software Specs

Wireless	Wi-Fi Standards	Wi-Fi 7	Network	QoS
	Max Wi-Fi Modulation	4K-QAM		DHCP
	Wi-Fi Efficiency	MLO		
		MRU		
		Puncturing		IP Versions
		OFDMA		IPv6 Protocols
		MU-MIMO		
		BSS Color		
	Max Capacity	512		
	Recommended Client Upper Limit	200		
	Max Wi-Fi Channel Width	160 MHz		
	Wi-Fi Security	WPA/WPA2/WPA3		
	Guest Network	2.4 GHz, 5 GHz		IPTV/VLAN
	WPS	True		
General	Operation Modes	Wi-Fi Router		
		Access Point		
	Multi-Band Backhaul	True		TTL Customization
	WAN Mode	DHCP		
		Static IP		
		PPPOE		IGMP
		PPTP		
		L2TP		

Per-User Rate Limiting
Address Reservation
DHCP Client List
Server
IPv4/IPv6
Relay
Dynamic (SLAAC/DHCPv6)
Static (Fixed IP)
Passthrough
464XLAT
MAP-E
DS-Lite
Bridge
Tag VLAN
VoIP VLAN
IPTV VLAN
Extend
Spoof
Custom
IGMP Proxy
IGMP Snooping



# Software Specs

Network	Forwarding	Port Forwarding	Utilities	VPN Client	WireGuard
		Port Triggering	_		OpenVPN
		UPnP	-		IPsec
		DMZ	_		Zerotier
	Firewall	SPI Firewall	_		PPTP
		DoS Protection	_		L2TP
		Block PING	_	DNS Options	DNS over TLS
	Application Layer Gateway	IPSec Passthrough			Manual DNS
		L2TP Passthrough	_		Rebind Protection
		PPTP Passthrough	_		Override Clients' DNS
		FTP Passthrough	_	DNS over TLS Providers	Cloudflare
		TFTP Passthrough	_		Google
		H323 Passthrough	-		Quad9
		SIP Passthrough			Custom
		RTSP Passthrough		Wake on LAN	True
Itilities	VPN Server	WireGuard	_	Online Detection	True
		OpenVPN	Management	All Devices Management	Wi-Fi Time Schedule
		IPsec	_		MAC Filter
		Zerotier	_		IP/MAC Binding
		PPTP		Per-Devices Management	Internet On/Off
		L2TP			VPN On/Off
			-		Online Time Schedule
					Device Rename



# Software Specs

System	LED Control	True	System	Languages
	Local Control Method	Config Web Page		
		App Control		
	Remote Control Method	Config Page via HTTPS	Dashboard	Panel
		App Control		
		TR069/TR098/TR111/TR181		
	Firmware Upgrade	Local Update		
		App (Over the Air)		
		Online Update		
	Reliability	Timed Reboot		
		Backup and Restore		
	Diagnostic Tools	Diagnosis		Charts
		Ping		
		Traceroute		
		NSLookup		
		System Log		
	Languages	• English • Bengali • Catalan • Czech		
		• German • Greek • Spanish • French		
		• Hebrew • Italian • Croatian • Hungarian		
		Khmer     Korean     Dutch     Japanese		
		• Russian • Slovak • Swedish • Romanian		

• Turkish • Vietnamese • Thai • Ukrainian			
Polish      Norwegian      Portuguese			
• Simplified Chinese • Traditional Chinese			
Internet Status			
Devices Management			
WAN Status			
LAN Status			
Wi-Fi Status			
VPN Status			
DHCP Server Status			
System Version			
Internet Speed			
Wi-Fi Speed			